



## NaturFelt™

### Acoustic floor material.

<b>The use</b>	NaturFelt™ is ideal for the floors. For new constructions or in renovation.
<b>Characteristics</b>	<ul style="list-style-type: none"> <li>Phonic product</li> <li>Water vapor permeable</li> <li>Natural resistance to pests</li> <li>Strong mechanical resistance</li> <li>Facilitated by implementation</li> <li>Hygrometric regulator</li> <li>Recoverable, recyclable material</li> <li>Renewable raw material</li> </ul>
<b>Composition</b>	100% hemp fibers
<b>Installation</b>	<p>Unroll product onto the subfloor and staple as required. To join edges, simply stick the felt strips together. Do not overlap product. Leave 1 cm gap between felt and wall. Can be cut with a round saw or a good scissors.</p> <p>Installation does not cause skin irritation.</p>
<b>Density</b>	750g / m <sup>2</sup>
<b>Thickness</b>	1/4"
<b>Size</b>	47 ¼" X 164'
<b>Package (roll)</b>	1
<b>Feet<sup>2</sup> / roll</b>	645 ft <sup>2</sup>
<b>Conditioning</b>	<p>Conditioned(packaged) by pallet of 4 rolls.</p> <p>Dimensions of the pallet: 40" X 40" X 52" high.</p>
<b>Storage</b>	Keep in a dry place and well covered.